NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

WARTIME REPORT

ORIGINALLY ISSUED

July 1943 as
Advance Restricted Report 3G30

5-16-47

EFFECT OF TURBULENCE ON AIR-FLOW MEASUREMENTS

BEHIND ORIFICE PLATES

By Jack N. Nielsen

Langley Memorial Aeronautical Laboratory
Langley Field, Va.

NACA

WASHINGTON

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

———————

ADVANCE RESTRICTED REPORT

———————

EFFECT OF TURBULENCE ON AIR-FLOW MEASUREMENTS

BEHIND ORIFICE PLATES

By Jack N. Nielsen

SUMMARY

Determinations of air-flow quantity have been made
in front of and behind three orifice plates to determine
the errors introduced in the quantity measurements by the
turbulence behind the orifice plates. For the orifice
plates tested, the results showed that the measurements
must be taken 40 to 60 hole diameters downstream from the
plates to insure accuracy. A tendency for the indicated
static pressure to rise during the decay of the turbulence
was found. In all cases, the indicated total pressure
dropped during the decay of turbulence.

INTRODUCTION

Orifice plates have come into general use for simulat-
ing radiators and other resistance elements in studies of
air flow in cooling ducts. Although orifice plates have
the advantage of much less scale effect than screens used
for this purpose, the large-scale turbulence that they in-
troduce interferes with the measurements of velocity and
pressure loss when these measurements must be made close
behind the plate. The purpose of the present investigation
conducted at Langley Memorial Aeronautical Laboratory was
to determine the variation of the magnitudes of the errors
in the measurements of velocity and pressure loss with
distance of the measuring tubes behind the orifice plate.

SYMBOLS

Q_o air-flow quantity measured in front of orifice plate

Q_i air-flow quantity measured behind orifice plate

q_o dynamic pressure at station upstream of orifice plate

p_o static pressure at station upstream of orifice plate

H_o total pressure at upstream face of orifice plate

p_i indicated static pressure at station behind orifice plate

H_i indicated total pressure at station behind orifice plate

APPARATUS AND METHODS

The duct system used in the tests is shown diagrammatically in figure 1. It consisted of a uniform rectangular test section of sheet metal, with a large wooden bell at the inlet and an expanding passage at the outlet leading to a variable-speed blower. The velocity of the entering air flow was measured by means of a network of static-pressure and total-pressure tubes placed in the throat of the bell (fig. 2). A similar network of tubes (fig. 3) was used for the downstream measurements, which were made at three different distances from the orifice plate: $9\frac{3}{4}$, $20\frac{3}{4}$, and $27\frac{3}{4}$ inches, as indicated in figure 1. The airspeed was about 67 feet per second for all tests. All pressures were recorded simultaneously by means of a 100-tube photographic manometer.

The three orifice plates tested, which are designated orifice plates 1, 2, and 3 (figs. 4, 5, and 6), were made of $\frac{3}{16}$-inch steel plate, with punched $\frac{3}{4}$-inch or $\frac{1}{2}$-inch holes. No effort was made to round off the edges formed by the punch. These edges faced upstream for orifice plates 1 and 2 and downstream for orifice plate 3. The direction in which the edges faced, however, produced no appreciable effect on the pressure-drop coefficient, according to reference 1. Orifice plate 3 had a design pressure-drop coefficient of 2.6 (reference 1). The other two plates had design pressure-drop coefficients of about 6.0 but differed in hole diameter. The characteristics of the three orifice plates are summarized in the following table:

Orifice plate	Ratio of open area to frontal area	Hole diameter (in.)	Design pressure-drop coefficient (from fig. 7 of reference 1)	Measured pressure-drop coefficient
1	0.391	3/4	6.3	6.8
2	.402	1/2	6.0	5.9
3	.540	3/4	2.6	2.0

RESULTS AND DISCUSSION

In figure 7 the ratio of the air-flow quantity indicated by the measurements behind the orifice plate to the true air-flow quantity indicated by the measurements in front of the orifice plate Q_i/Q_o is plotted against distance behind the orifice plate. Simple arithmetic averages of the indicated velocities were used in computing these air-flow quantities. With orifice plate 1, which had the highest pressure drop, Q_i was 16 percent too high when measured $9\frac{3}{4}$ inches behind the plate and 5 percent too high at $27\frac{3}{4}$ inches behind the plate. With orifice plate 3, which had the lowest pressure drop, Q_i was too high by 7 percent and 2.5 percent, respectively, at these two stations. It is likely that at least part of the error at the downstream station is due to the absence of measuring tubes in the low-velocity boundary layer along the wall. This error did not exist in the measurement of Q_o because the boundary layer at the bell throat was very thin.

It appears, then, that for orifice plates of the type investigated, air-flow quantities measured behind the plate will be considerably too high unless the measuring tubes are between 40 and 60 hole diameters downstream from the plate. This length of duct will hardly be available, however, unless the orifices are smaller than those used in these tests. For example, if scale effect is negligible, $\frac{1}{4}$-inch orifices would be satisfactory in a full-scale simulated ethylene-glycol radiator duct. For this case, the orifice plate would be placed where the front face of the radiator would be and the measuring tubes would be placed 10 or 12 inches farther back, where the rear face would be.

In figures 8, 9, and 10 the pressure-drop coefficients, as determined from the readings of both the static-pressure

4

tubes and the total-pressure tubes, are plotted against
distance behind the orifice plate. Behind orifice plates
1 and 2, the measured static pressure p_1 tends to in-
crease along the passage; the pressure drop determined
from the static-pressure measurements correspondingly
decreases. At least part of this static-pressure rise
is due to a transformation of a portion of the random
kinetic energy to static pressure during the decay of the
turbulence.

The measured total pressure H_1 decreases along the
passage, and the pressure drop determined from the total-
pressure measurements correspondingly increases. Here,
again, part of the effect is due to the decay of the tur-
bulence. The decrease in the measured total pressure is
due to the following factors: First, the readings of a
total-pressure tube in a turbulent flow are increased by
a dynamic pressure based on the mean square of the turbu-
lent velocities (reference 2); and, second, this dynamic
pressure is not entirely recovered as total pressure dur-
ing the decay of the turbulence. The two types of pressure-
drop determination nearly agree where the error in the
measurement of the air-flow quantity becomes small — that
is, at 40 to 60 hole diameters downstream from the orifice
plate.

It will be noted that the relative errors in the
pressure-drop determination were, at least for orifice
plates 1 and 2, less than the errors in the determination
of the air-flow quantity. Thus, the maximum difference of
the pressure-drop coefficients measured behind the orifice
plate is only about 5 percent of their mean value in fig-
ures 8 and 9 and about 8 percent in figure 10.

CONCLUSIONS

1. Measured air-flow quantities may be 10 to 15 per-
cent too high if the measuring tubes are 15 to 20 hole
diameters behind an orifice plate. A distance of 40 to 60
hole diameters must be used for accuracy.

2. Pressure drops as determined from total-pressure-
tube readings increase with distance of the tubes from the
orifice plate; pressure drops as determined from static-
pressure-tube readings tend to decrease with distance of
the tubes from the orifice plate. For the orifice plates

tested, the two pressure drops become nearly equal at 40 to 60 hole diameters behind the plate, where the intensity of the turbulence in the air flow is greatly decreased.

REFERENCES

1. Czarnecki, K. R.: Pressure-Drop Characteristics of
        Orifice Plates Used to Simulate Radiators. NACA
        A.R.R., March 1942.

2. Goldstein, S.: A Note on the Measurement of Total Head
        and Static Pressure in a Turbulent Stream. Proc.
        Roy. Soc. (London), ser. A, vol. 155, no. 886,
        July 1, 1936, pp. 570-575.

Figure 1.- Schematic diagram of test section.

Fig. 1

L-274

Figure 2.- Upstream network of static-pressure and total-pressure tubes.

⊗ Static pressure   ⊙ Total pressure

Figure 3.- Downstream network of static-pressure and total-pressure tubes.

⊗ Static pressure   ⊙ total pressure

Figure 4.- Orifice plate 1.

Figure 5.- Orifice plate 2.

Figure 6.- Orifice plate 3.

Figure 7.— Error in flow-quantity measurements downstream of orifice plate.

Figure 8.— Orifice-plate pressure-drop coefficients as measured by static-pressure and total-pressure tubes. Orifice plate 1.

Figure 9.- Orifice-plate pressure-drop coefficients as measured by static-pressure and total-pressure tubes. Orifice plate 2.

Figure 10.— Orifice-plate pressure-drop coefficients as measured by static-pressure and total-pressure tubes. Orifice plate 3.